

Easily removes adhesive from a wide variety of material surfaces. A water-soluble and nonflammable formula.



Where To Use

Detail Shops	Poly Banners	Residues on Painted Aluminum
Glass	Polycarbonates	Removing Window Tinting
Vinyl	Auto Paint	Removing Decals
Plexiglass		

Directions

Once the vinyl or decal graphics have been removed with heat, use the spray on the remaining adhesive. Allow to stand on the surface for 30 seconds - more difficult jobs may require more standing time. Use a dry cloth or squeegee to wipe away the residue, then rinse thoroughly with water. Paint must be completely cured before application. Use only on oil-based enamel surfaces. This spray is not recommended for use on latex paint backgrounds.

Technical Specifications

CAN SIZE: ...16 oz.	NET WEIGHT:14 oz.
ODOR:Citrus	USDA RATING:N/A
TYPE:Aerosol	PROPELLANT:Hydrocarbon
pH:9.4	SPRAY PATTERN:....Foamy Stream
COLOR:White Foam	FLAMMABILITY:....None - per CPSC Flame
	Ext. Test in 16 CFR 1500.45.



201 Boston Turnpike, Bolton, CT 06043-7203 800-227-5536 • 860-646-0172 • FAX 860-645-6070

www.simoniz.com www.simonizjanitorial.com

All labels are GHS compliant.