

The first step in a two step cleaning system, used before applying KOLD KLEEN 2 as the second step cleaner. Removes oily soils and helps break the static bond that causes dirt to cling to painted surfaces.



Where To Use

Truck Fleets Construction Equipment

Dilution and Directions

KOLD KLEEN I and KOLD KLEEN II should never be mixed together in the same container. This product is ready through a pressure washer at 1/25, with cold water. Check the machine manufacture's recommendation as to suitability of pressure washer for acid use. Otherwise acid must be injected with a pump saver injector or similar device. Avoid applying on windy days and before washing always check suitability for use on surface to be cleaned. It is always best to wash from the bottom up. After applying Kold Kleen I follow with application of Kold Kleen II at proper dilution, and finally pressure rinse clean with cold water pressure washer. Do Not allow to dry on glass. Be sure to wet and keep wet windshields and glass.

Technical Specifications

COLOR: Transparent Blue	VISCOSITY: Water Thin
FORM: Liquid	STORAGE(Unopened):...1 Year @R.T.
SCENT: Irritating	BIODEGRADABLE: ...Yes
pH: < 1.0	WEIGHT/GAL:10.1 lbs.
FLASH POINT: None	SHIPPING CLASS:8, Packing Gr II
FOAM: Low	PACKAGING:5 gal, 55 gal
TYPE: Hydroflouric Acid 1st Step Truck Wash	

