

A thixotropic, highly alkaline paint stripper formulated to remove multiple layers of paint. Contains no harsh solvents.



Where To Use

Do not use on Aluminum or Magnesium.

Brick Wood Surfaces

Stone Metal Surfaces

Dilution

As is

Directions

Determine number of layers of stripping job by scraping out a paint chip. Put down a test patch to find out how long it takes stripper to work through layers (from 1-24 hours). A very difficult job may take 2 coats. Apply ML Stripper with a large, sort bristle brush or drizzle spray with an airless sprayer (minus the nozzle). If the area is exposed to the sun, water mist occasionally. The surface should be kept moist. When paint has softened, pressure rinse clean. If a second coat of stripper is required, apply subsequently. Neutralize surface with a finishing rinse of Simoniz® Restore diluted 1/10.

Technical Specifications

COLOR:	Gold	VISCOSITY:	Viscous
FORM:	Liquid	STORAGE(Unopened):..	1 Year @R.T.
SCENT:	Odorless	BIODEGRADABLE: ...	Yes
pH:	14.0	WEIGHT/GAL:	> 8.3 lbs.
FLASH POINT:	None	SHIPPING CLASS:	8, Packing Gr II
FOAM:	N/A	PACKAGING:	5 gal, 55 gal
TYPE:	Caustic paint stripper		

