











sealtite®

Use & Specifications

USE

 <p>Formulated for use in on-highway heavy duty trucks. Acts as a flat preventative and hydrodynamic balancer. Can also be used for industrial equipment, agricultural equipment, cars, light trucks, etc.</p>	 <p>Formulated for tires traveling less than 45 mph. Seals punctures in tires on industrial equipment, agricultural equipment and other large and small slow moving tires.</p>	 <p>Formulated for use in tires filled with a liquid ballast solution. May be mixed with any ballast solution including those containing calcium chloride, antifreeze (glycol).</p>	 <p>Formulated to reduce heat and condition tire and rim.</p>
---	---	---	--

SPECIFICATIONS

				
PHYSICAL APPEARANCE:	yellow	green	white	orange
FREEZING POINT:	-34° F (-37° C)	-34° F (-37° C)	N/A*	-34° F (-37° C)
OPERATING TEMPERATURE:	240° F (116° C)	240° F (116° C)	N/A*	240° F (116° C)
CHEMICAL CONTENT:	Proprietary blend of multi length ceramic fibers suspended homogeneously in a water/glycol base solution containing various inhibitors (rust, corrosion, antibacterial) . • LIFE X-TEND DOES NOT CONTAIN FIBERS			
SOLUBILITY IN WATER:	High solubility for easy clean up and removal			
FIRE / EXPLOSION HAZARDS:				
pH:				
PROTECTED METALS	aluminum, steel, brass, copper, iron, chrome, magnesium alloy	N/A*	aluminum, steel, brass copper, iron chrome, magnesium alloy	
HEALTH HAZARDS:	This product contains a glycol solution and should not be taken internally. It is recommended that the user avoid prolonged breathing of product vapors. The user should wear protective eye goggles and avoid product contact with the eyes. There is no evidence of any adverse health absorption. General room ventilation is adequate at ambient temperatures.			
For additional information refer to MSDS				