

Ammoniated Speed Strip

A0040

An economical, concentrated stripper fortified with ammonia for quick removal of floor finishes from all types of resilient tile floors.



Tip: For Best Results – use separate mop and bucket (or replacable plastic liner) for stripper and finish.

Where To Use

Vinyl Tile	Linoleum	Sealed Wood
Stone	Rubber Tile	Asbestos Tile
Concrete	Asphalt Tile	Terrazzo

Dilution

Heavy stripping – 1/4 (32 oz./gallon)
Medium – 1/8 (16 oz./gallon)
Light – 1/16 (8 oz./gallon)

Directions

Dust mop and scrape gum, etc. from floor. Determine dilution from table above and add appropriate amount of product to warm water. Apply solution generously to a workable area. Allow solution to sit for 5-10 minutes. Floor must remain wet. Agitate solution with floor machine using an aggressive stripping pad (black or brown). If needed, hand scrub edges and corners with edge pad or center of the scrubbing pad. Pick up loosened finish and stripper with wet vac or mop. Rinse thoroughly. Inspect entire floor to ensure stripping has been complete. Reapply to areas that require additional stripping. Allow floor to dry completely prior to applying sealer or finish.

Technical Specifications

COLOR: Transparent	VISCOSITY: Water Thin
FORM: Liquid	STORAGE(Unopened):..1 Year @R.T.
SCENT: Ammonia	BIODEGRADABLE: ...Yes
pH: 12.3	WEIGHT/GAL:8.3
FLASH POINT: None	SHIPPING CLASS:None
FOAM: None	PACKAGING:4x1, 5 gal, 55 gal
TYPE: Ammoniated Stripper	

