

A very low odor, non-corrosive, non-butyl floor sealer and finish remover. Specially designed to remove new zinc-free finishes.



Where To Use

Vinyl Tile Asbestos Tile
Concrete Terrazzo
Stone Asphalt Tile

Dilution

Light to Medium finish build-up – 1/7 - 1/10
Heavy soil loads finish build-up – 1/3 - 1/6

Directions

Dust mop and scrape gum, etc. from floor. Dilute according to the above directions. Apply the solution generously to workable area. Allow solution to sit for 5 to 10 minutes. Floor must remain wet. Agitate solution with floor machine using an aggressive stripping pad (black or brown) if needed hand scrub edges and corners with and edge pad or center of the scrubbing pad. Pick up solution and old finish with a wet vac or mop and bucket. Inspect entire floor to ensure complete stripping has been accomplished. Reapply when necessary. Rinse thoroughly with cool clear water. Allow floor to dry completely prior to applying sealer or finish.

Technical Specifications

COLOR:	Transparent	VISCOSITY:	Water Thin
FORM:	Liquid	STORAGE(Unopened):...	1 Year @R.T.
SCENT:	Wintergreen	BIODEGRADABLE: ...	Yes
pH:	11.7	WEIGHT/GAL:	8.3
FLASH POINT:	None	SHIPPING CLASS:	None
FOAM:	Low	PACKAGING:	4x1 gal, 2x2.5 gal
TYPE:	Floor Stripper		

