

A zinc-free floor sealer and finish containing no heavy metals. It has a low odor finish with exceptional gloss that can be maintained with scrub and re-coat procedures, spray buffing or high speed burnishing.



Where To Use

Vinyl Tile Linoleum Sealed Wood
Terrazzo Rubber Tile Asbestos Tile
Asphalt Tile Concrete

Dilution

This product is ready-to-use.

Directions

Prior to use ensure that the floor has been completely stripped of all old finish, scrubbed or cleaned. The floor should be completely dry before applying the first coat and all subsequent coats. Apply undiluted ZF-25 evenly in thin coats. 5 to 6 coats may be required if the floor is old or in poor condition. Make sure to use a different mop for stripping and applying finish. Allow 24 hours for curing before burnishing. For superior results, use with regular weekly UHS burnishing.



Technical Specifications

COLOR: White	TYPE: Floor Finish
FORM: Liquid	SOLID CONTENT: 25%
SCENT: Mild Solvent/Polymer	RECOAT DRYING TIME: 30 minutes
pH: 8.0-9.0	COVERAGE: 2500 - 3000 sq ft
FLASH POINT: None	SLIP COEFFICIENT: 0.5
FOAM: None	REMOVABILITY: Excellent
LEVELING: Excellent	SCUFF RESISTANCE: Excellent
VISCOSITY: Water Thin	DETERGENT RESISTANT: . Excellent
STORAGE(Unopened): . 1 Year @R.T	HIGH SPEED BURNISH: Yes
BIODEGRADABLE: Yes	PACKAGING: 4x1 gal, 22x2.5 gal
WEIGHT/GAL: 8.4	
SHIPPING CLASS: None	

